



**0640 Series**  
Frameless Mirrors  
with LED Backlight



**0641 Series**  
Frameless Mirrors  
with LED Backlight  
and Frosted Border

# BACKLIGHTING THAT REFLECTS GREAT DESIGN

**Add light to where it's needed the most** with ASI's new frameless plate glass mirrors with LED backlight. Combining style with functionality, these mirrors are a perfect fit for any washroom aesthetic from offices to hospitality settings, and are available with frosted borders for extra choice.

## FEATURES / BENEFITS:

- 5/32" (4 mm) frameless plate glass with polished edges for user safety
- Glows at 6000 Kelvin
- LED bulbs offer an average savings of \$100 per year\* and can have a lifespan of over 50,000 hours.
- Connected through power cord or hardwired
- Can be mounted vertically or horizontally
- Projects 1 3/4" from the wall
- 5 year warranty

*\*based on 6 hours per day, 7 days per week*

**0640 SERIES** adds wall accent and soft lighting around the mirror

MODEL NUMBER	OVERALL SIZE ( W x H )	LUMENS
0640-2436	24" X 36" (610 X 914 mm)	2352
0640-3036	30" X 36" (762 X 914 mm)	2640
0640-4836	48" X 36" (1219 X 914 mm)	3514
0640-6036	60" X 36" (1524 X 914 mm)	4128

**0641 SERIES WITH FROSTED BORDER** illuminates the front and sides of the mirror

MODEL NUMBER	OVERALL SIZE ( W x H )	LUMENS
0641-2436	24" X 36" (610 X 914 mm)	2352
0641-3036	30" X 36" (762 X 914 mm)	2640
0641-4836	48" X 36" (1219 X 914 mm)	3514
0641-6036	60" X 36" (1524 X 914 mm)	4128

## **0640 SERIES FRAMELESS MIRRORS WITH LED BACKLIGHT**

## **0641 SERIES FRAMELESS MIRRORS WITH LED BACKLIGHT AND FROSTED BORDER**

---

### **SPECIFICATION**

- Frameless polished edge mirror with integral aluminum mounting frame and frosted glass border LED halo lighting shall be consistent with A glazing (plate glass) and shall be 5/32" [4] thick.
- Hard wired LED lighting system shall be UL listed and shall operate on 100/240 VAC 50/60 Hz.
- Light color shall be the equivalent of 6000 K.
- Unit shall be mountable in horizontal or vertical format without additional brackets or adaptations to mounting provisions.
- Power cord is included for use by owner if appropriate socket is provided on wall (by others) concealed by mounting frame of mirror and is 34" [86] long with 3-prong USA pattern plug and bare wires for connection to hard wiring in LED control box.
- Mirror glass and LED system shall be warranted for manufacturing defects for a period of five (5) years from ship date.
- Keyhole mounting slots are provided for installation in long and short sides of back frame. Mirror is to be hung on pre-installed pan head screws (provided) to be retained by screw heads engaged into the slots.

